

NO HUB PIPE. 10' LAYING LENGTH

Size	Wt/Piece(Kgs)	Wt/Piece(Lbs)	Pieces/Bundle	Kgs/Bundle	Lbs/Bundle
1 1/2"	13.0	29	84	1092	2407
2"	16.3	36	68	1108	2444
3"	23.5	52	44	1034	2280
4"	33.5	74	30	1005	2216
5"	42.6	94	21	895	1972
6"	51.0	112	18	918	2024
8"	82.2	181	10	822	1812
10"	130.0	287	8	1040	2293
12"	148.0	326	6	888	1958
15"	241.8	533	3	725	1599

DIMENSIONS AND TOLERANCES

Size	Wt/Piece(Lbs)	ID	OD	Norm T	Min T
1 1/2"	29	1.50±06	1.90±06	0.16	0.13
2"	36	1.96±09	2.35±09	0.16	0.13
3"	52	2.96±09	3.35±09	0.16	0.13
4"	74	3.94±09	4.38+.09/-.05	0.19	0.15
5"	94	4.94±09	5.30+.09/-.05	0.19	0.15
6"	112	5.94±09	6.30+.09/-.05	0.19	0.15
8"	181	7.94±13	8.38+.13/-.09	0.23	0.17
10"	287	10.00±13	10.56±09	0.28	0.22
12"	326	11.94±13	12.50±13	0.28	0.22
15"	533	15.11±13	15.83±13	0.35	0.3

No Hub Pipe conform to ASTM A 888 and CISPI 301.

Mechanical Properties: Tensile Strength not less than 21000psi (145Mpa).

Straightness of Pipe: Deflections not exceed 5/8"(16mm).

Hydraulic Pressure Test: 0.45Mpa (65psi)

Cut: Smooth by snap cutter.

Unit Weight: Actual unit weight and never decorate wall thickness.

Packing: Pipes are bundled with 7 strips steel bands and lay on solid wooden pallet.

Contact: Mr. Li Zhiyong

Mobile: +86-18500608262

Skype: qslizy

Email: lizy@qiaoshan.co

www.qiaoshan.co

