

NO HUB PIPE. 10' LAYING LENGTH

Size	Wt/Piece(Kgs)	Wt/Piece(Lbs)	Pieces/Bundle	Kgs/Bundle	Lbs/Bundle
1 1/2"	13.00	29	84	1092	2407
2"	16.00	35	68	1088	2399
3"	23.00	51	44	1012	2231
4"	34.40	76	30	1032	2275
5"	43.00	95	21	903	1991
6"	51.00	112	18	918	2024
8"	82.20	181	10	822	1812
10"	130.00	287	8	1040	2293
12"	148.00	326	6	888	1958
15"	241.80	533	3	725	1599

DIMENSIONS AND TOLERANCES

Size	Min ID (in)	Min OD (in)	Max OD (in)	Min Thickness
1 1/2"	1.42	1.84	2.00	0.12
2"	1.91	2.28	2.48	0.12
3"	2.92	3.32	3.50	0.13
4"	3.94	4.36	4.56	0.15
5"	4.98	5.40	5.56	0.15
6"	5.92	6.40	6.64	0.15
8"	7.88	8.52	8.76	0.17
10"	9.84	10.68	10.64	0.22
12"	11.88	12.72	12.88	0.22
15"	14.80	15.88	16.08	0.30

No Hub Pipe conform to CSA B70.

Mechanical Properties: Tensile Strength not less than 21000psi (145Mpa).

Straightness of Pipe: Deflections not exceed 5/8"(16mm).

Hydraulic Pressure Test: 0.45Mpa (65psi)

Cut: Smooth by snap cutter.

Unit Weight: Actual unit weight and never decorate wall thickness.

Packing: Pipes are bundled with 7 strips steel bands and lay on solid wooden pallet.

Contact: Mr. Li Zhiyong

Mobile: +86-18500608262

Skype: qslizy

Email: lizy@qiaoshan.co

www.qiaoshan.co

