

Flexible Coupling



Contact: Mr. Li Zhiyong (Owner)

Mobile(Whatsapp): +86-13467138000

Skype: qslizy

E-mail: qscasting@126.com


www.qiaoshan.co





Tel: 86 10 64644308


Fax: 86 10 64644308


Room 256, Building 1, No. 35 Zhenxing Road, Changping, Beijing 102200


Flexible Couplings 1001 Series - Clay to Clay			Material& Technical Specs
	1001-44	4" x 4"	<ul style="list-style-type: none"> • 12.7 inches wide • 3/8 inch thick with multiple sealing ribs • 2 - Series 300 (18-8) all stainless steel, extra strength (.040 in. thick) T-bolt clamps with multiple take up points • Up to 150 in./lbs. of torque • Flexible PVC • Conforms to ASTM C1173 and CSA B602
	1001-54	5" x 4"	
	1001-55	5" x 5"	
	1001-64	6" x 4"	
	1001-65	6" x 5"	
	1001-66	6" x 6"	
	1001-86	8" x 6"	
	1001-88	8" x 8"	
	1001-10-8	10" x 8"	
	1001-1010	10" x 10"	
	1001-1210	12" x 10"	
	1001-1212	12" x 12"	


Flexible Couplings 1002 Series - Clay to Cast Iron or Plastic			Material& Technical Specs
	1002-43	4" x 3"	<ul style="list-style-type: none"> • 12.7 inches wide • 3/8 inch thick with multiple sealing ribs • 2 - Series 300 (18-8) all stainless steel, extra strength (.040 in. thick) T-bolt clamps with multiple take up points • Up to 150 in./lbs. of torque • Flexible PVC • Conforms to ASTM C1173 and CSA B602
	1002-43EC	Eccentric Coupling	
	1002-44EC	Eccentric Coupling	
	1002-46	4" x 6"	
	1002-54	5" x 4"	
	1002-55	5" x 5"	
	1002-64	6" x 4"	
	1002-65	6" x 5"	
	1002-66	6" x 6"	
	1002-86	8" x 6"	
	1002-88	8" x 8"	
	1002-10-8	10" x 8"	
	1002-1010	10" x 10"	
	1002-1210	12" x 10"	
	1002-1212	12" x 12"	
1002-1212EC	Eccentric Coupling		


1003 Series - Clay to Asbestos Cement Fibre or Ductile Iron			Material& Technical Specs
	1003-44	4" x 4"	<ul style="list-style-type: none"> • 12.7 inches wide • 3/8 inch thick with multiple sealing ribs • 2 - Series 300 (18-8) all stainless steel, extra strength (.040 in. thick) T-bolt clamps with multiple take up points • Up to 150 in./lbs. of torque • Flexible PVC • Conforms to ASTM C1173 and CSA B602
	1003-46	4" x 6"	
	1003-55	5" x 5"	
	1003-64	6" x 4"	
	1003-66	6" x 6"	
	1003-86	8" x 6"	
	1003-88	8" x 8"	
	1003-10-8	10" x 8"	
	1003-1010	10" x 10"	
	1003-1210	12" x 10"	
1003-1212	12" x 12"		


Flexible Couplings 1004 Series - Concrete to Concrete			Material& Technical Specs
	1004-44	4" x 4"	<ul style="list-style-type: none"> • 12.7 inches wide • 3/8 inch thick with multiple sealing ribs • 2 - Series 300 (18-8) all stainless steel, extra strength (.040 in. thick) T-bolt clamps with multiple take up points • Up to 150 in./lbs. of torque • Flexible PVC • Conforms to ASTM C1173 and
	1004-64	6" x 4"	
	1004-66	6" x 6"	
	1004-86	8" x 6"	
	1004-88	8" x 8"	
	1004-10-8	10" x 8"	
	1004-1010	10" x 10"	
	1004-1210	12" x 10"	
	1004-1212	12" x 12"	

Flexible Couplings 1006 Series -Concrete to Cast Iron or Plastic			Material& Technical Specs
	1006-43	4" x 3"	<ul style="list-style-type: none"> • 12.7 inches wide • 3/8 inch thick with multiple sealing ribs • 2 - Series 300 (18-8) all stainless steel, extra strength (.040 in. thick) T-bolt clamps with multiple take up points
	1006-44	4" x 4"	
	1006-46	4" x 6"	
	1006-64	6" x 4"	
	1006-65	6" x 5"	
	1006-66	6" x 6"	
	1006-86	8" x 6"	
	1006-88	8" x 8"	


Flexible Couplings 1006 Series -Concrete to Cast Iron or Plastic			Material& Technical Specs
	1006-10-8	10" x 8"	<ul style="list-style-type: none"> • Up to 150 in./lbs. of torque • Flexible PVC • Conforms to ASTM C1173 and CSA B602
	1006-1010	10" x 10"	
	1006-1210	12" x 10"	
	1006-1212	12" x 12"	


Flexible Couplings 1051 Series - Asbestos Cement Fibre (AC) or Ductile Iron to Cast Iron or Plastic			Material& Technical Specs
	1051-43	4" x 3"	<ul style="list-style-type: none"> • 12.7 inches wide • 3/8 inch thick with multiple sealing ribs • 2 - Series 300 (18-8) all stainless steel, extra strength (.040 in. thick) T-bolt clamps with multiple take up points • Up to 150 in./lbs. of torque • Flexible PVC • Conforms to ASTM C1173 and CSA B602
	1051-44	4" x 4"	
	1051-54	5" x 4"	
	1051-55	5" x 5"	
	1051-64	6" x 4"	
	1051-65	6" x 5"	
	1051-66	6" x 6"	
	1051-86	8" x 6"	
	1051-88	8" x 8"	
	1051-10-8	10" x 8"	
	1051-1010	10" x 10"	
	1051-1210	12" x 10"	
1051-1212	12" x 12"		

Flexible Couplings 1055 Series - AC or Ductile Iron to AC or Ductile Iron			Material& Technical Specs
	1055-44	4" x 4"	<ul style="list-style-type: none"> • 12.7 inches wide • 3/8 inch thick with multiple sealing ribs • 2 - Series 300 (18-8) all stainless steel, extra strength (.040 in. thick) T-bolt clamps with multiple take up points • Up to 150 in./lbs. of torque • Flexible PVC • Conforms to ASTM C1173 and CSA B602
	1055-54	5" x 4"	
	1055-55	5" x 5"	
	1055-64	6" x 4"	
	1055-65	6" x 5"	
	1055-66	6" x 6"	
	1055-86	8" x 6"	
	1055-88	8" x 8"	
	1055-10-8	10" x 8"	
	1055-1010	10" x 10"	
	1055-1210	12" x 10"	
	1055-1212	12" x 12"	

Flexible Couplings 1056 Series - CI, PL, Copper, ST or Lead to CI, PL, Copper, ST or Lead		Material& Technical Specs
	1056-100	1" x 1"
	1056-125	1-1/4" x 1-1/4"
	1056-150/125	1-1/2" x 1-1/4"
	1056-150	1-1/2" x 1-1/2"
	1056-215	2" x 1-1/2"
	1056-22	2" x 2"
	1056-315	3" x 1-1/2"
	1056-32	3" x 2"
	1056-33	3" x 3"
	1056-415	4" x 1-1/2"
	1056-415EC	4" x 1-1/2" EC
	1056-42	4" x 2"
	1056-43EC	4" x 3" EC
	1056-44	4" x 4"
	1056-53	5" x 3"
	1056-54	5" x 4"
	1056-55	5" x 5"
	1056-63	6" x 3"
	1056-64EC	6" x 4" EC
	1056-65	6" x 5"
	1056-65EC	6" x 5" EC
	1056-66	6" x 6"
	1056-84	8" x 4"
	1056-84EC	8" x 4" EC
	1056-86EC	8" x 6" EC
1056-88	8" x 8"	
1056-10-6EC	10" x 6" EC	
1056-10-8	10" x 8"	
1056-10-8EC	10" x 8" EC	
1056-1010	10" x 10"	
1056-12-8EC	12" x 8" EC	
1056-1210	12" x 10"	
1056-1210EC	12" x 10" EC	
1056-1212	12" x 12"	

- 12.7 inches wide
- 3/8 inch thick with multiple sealing ribs
- 2 - Series 300 (18-8) all stainless steel, extra strength (.040 in. thick) T-bolt clamps with multiple take up points
- Up to 150 in./lbs. of torque
- Flexible PVC
- Conforms to ASTM C1173 and CSA B602

Flexible Couplings 159 Series - Plastic Socket to Plastic Pipe			Material& Technical Specs
	1059-150	1-1/2" x 1-1/2"	
	1059-22	2" x 2"	
	1059-33	3" x 3"	
	1059-44	4" x 4"	

1060 Series - Plastic Socket to Plastic Socket			Material& Technical Specs
	1060-150	1-1/2" x 1-1/2"	
	1060-22	2" x 2"	
	1060-33	3" x 3"	
	1060-44	4" x 4"	